



CUSHMAN®

HAULER® PRO-X



GET MORE MILEAGE OUT OF EVERY WORK DAY.

Stand back and let the new Hauler® PRO-X raise your expectations on what a 72-volt AC powertrain can do. With its 50-mile range, silent operation and lifted suspension, the Hauler PRO-X will help you and your team work seamlessly without disrupting your environment. Outstanding energy efficiency, low operational costs and a dash that easily accommodates radios, clip boards, oversized beverage containers and more, the Hauler PRO-X is equipped for action.

LET'S WORK.®

72V
AC
ELECTRIC

1200LB
TOW
CAPACITY

12 CU FT
CARGO
BED

900LB
LOAD
CAPACITY



CUSHMAN® HAULER® PRO-X



HIGHER GROUND CLEARANCE



STANDARD ON BOARD CHARGER



ROTO-MOLDED BED



VERSATILE DASH STORAGE

OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- L-Track Aluminum Bed System
- Weather Enclosure
- USB Outlet
- 12-Volt Outlet
- Canopy Storage Net
- Brushguard
- Rearview Mirror
- ROPS-Certified Cab
- Ladder/Hoop Rack
- Brake Lights
- Tail Lights
- 20" Improved surface tires
- E-Shield Frame
- Premium Steering Wheel



BODY & CHASSIS	
FRAME	Welded Steel with DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Patriot Blue
DIMENSIONS	
OVERALL LENGTH	119 in (302.3 cm)
OVERALL WIDTH	49.4 in (125.5 cm)
OVERALL HEIGHT W/ CANOPY	77 in (195.6 cm)
WHEEL BASE	77.5 in (196.9 cm)
FRONT WHEEL TRACK	38.0 in (96.5 cm)
REAR WHEEL TRACK	38.0 in (97.8 cm)
GROUND CLEARANCE	7.2 in (18.29 cm)
CARGO BOX CAPACITY	12 cu ft (.034 m ³)
POWER	
POWER SOURCE	72-Volts
MOTOR TYPE	AC Induction
HORSEPOWER (KW)	22.4HP (16.7 kW) - Measured at Peak Torque
ELECTRICAL SYSTEM	72 Volt
BATTERY (QTY/TYPE)	Nine 8-Volt Deep Cycle
BATTERY CHARGER	900 Watt 72V DC
KEY OR PEDAL START	Pedal
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential with Helical Gears
SPEED CONTROLLER	350 Amp AC
GEAR SELECTION	Forward-Neutral-Reverse
REAR AXLE RATIO	17:1
PERFORMANCE	
SEATING CAPACITY	2 Person
CURB WEIGHT	1513 lb (686 kg)
BED LOAD CAPACITY	500 lb (227 kg)
VEHICLE LOAD CAPACITY	900 lb (408 kg)
SPEED	16.5 mph ± 0.5 mph (26.6 kph ± 0.8 kph)
TOWING CAPACITY	1200 lb (544 kg) max
OUTSIDE CLEARANCE CIRCLE	23.5 ft (7.2 m)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack and Pinion
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum
PARKING BRAKE	Self-compensating, Single Point Engagement
FRONT/REAR TIRES	20 x 8.00 -10