



# SHUTTLE™ 6

## ACCELERATE GROUP TRANSPORTATION.

Comfortably and effectively move up to six people with the use of the four forward-facing seats and two rear-facing seats in the Shuttle 6. Available as an ELiTE lithium vehicle activated by Samsung SDI battery technology or with an efficient 13.5 hp EFI gasoline engine, the Shuttle 6 gives you the ability to take care of every task across your facility.

**6 PASSENGER**  
SEATING

**544 KG (1200LB)**  
VEHICLE LOAD CAPACITY

**EASY INGRESS**  
AND REGRESS

**ELiTE**  
LITHIUM



### NEVER BE OUTWORKED

Cushman® has been trusted for decades to produce long-lasting, dependable vehicles, but that's just the start. Cushman is continually pushing forward—with the unmatched, energyefficient performance of our ELITE lithium powertrain, and better riding, better-looking, vehicles that can be customized to your needs.

### KEY FEATURES

- Move up to six passenger
- Excellent 360 degree exterior view
- Easy ingress and regress
- Durable steel frame assure a comfortable ride

### BUILD YOUR VEHICLE

Visit [Cushman.com](https://cushman.com) to customize the vehicle for your task, by choosing the right model, powertrain, color, accessories, and more.

### KEY OPTIONS & ACCESSORIES

- Upgradeable Battery pack options (with 5-Year Battery Warranty)
- Rapid On-Board Charger (ELITE Only)
- Foldable rear seat
- Turn Signal with Four-Way Flashers
- Roof and Screen
- PACE Geofencing and GPS System

Explore all options and accessories on the website or contact your local dealer.

**CUSHMAN.COM**

# SHUTTLE™ 6

## BODY & CHASSIS

	SHUTTLE 6 ELITE	SHUTTLE 6 GASOLINE
FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Patriot Blue	

## DIMENSIONS

OVERALL LENGTH	343 cm (134 in)	
OVERALL WIDTH	123 cm (48.5 in)	
OVERALL HEIGHT	123 cm (48.5 in) (w/o Roof) / 183 cm (72.0 in) (w/ Struts & Roof)	
WHEEL BASE	237 cm (93.5 in)	
WHEEL TRACK	87 cm (34.2 in) Front / 97 cm (38.0 in) Rear	
GROUND CLEARANCE	9.8 cm (3.9 in)	11 cm (4.3 in)

## POWER

POWER SOURCE	56.7V Li-Ion Battery	4-Cycle, 401cc (24.5 ci)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	11.1 kW (14.9 hp)	10.1 kW (13.5 hp)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	56.7V Li-Ion Composite Module + Cell Model	One, 12V Maintenance Free
BATTERY CHARGER	56VDC, 120/230 VAC, UL/CSA, CE	N/A
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replaceable Industrial Rated Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	22.6 L (5.96 Gallon) tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash Mount Forward- Neutral- Reverse/Key Switch	Forward-Reverse
REAR AXLE RATIO	16.99:1	11.47: 1 (Forward) / 14.35:1 (Reverse)

## PERFORMANCE

SEATING CAPACITY	6-Person	
WEIGHT W/O BATTERIES	429 kg (945 lb)	510 kg (1124 lb)
CURB WEIGHT	465 kg (1026 lb)	528 kg (1164 lb)
VEHICLE LOAD CAPACITY	544 kg (1200 lb)	
OUTSIDE CLEARANCE CIRCLE	7.8 m (25.5 ft)	
SPEED	26.4 km/h ± 0.8 km/h (16.5 mph ± 0.5 mph)	22.5 km/h ± 0.8 km/h (14 mph ± 0.5 mph)

## STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum	
PARKING BRAKE	Automatic Electro-Magnetic	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	18 x 8.50 - 8 (4 Ply Rated)	