



HAULER[®] 1200 SERIES

RELENTLESS POWER TO OVERCOME THE TOUGHEST TASKS.

The Hauler 1200 Series is equipped to handle any job on your facility. A large bed providing essential functionality can easily be converted for any task. Featuring integrated tie-downs, a 0.34 M³ cargo bed and higher ground clearance with the Hauler 1200X, transporting tools and supplies has never been easier. Your work is unforgiving, expect nothing less than the best with the Hauler 1200 Series.

13.5 HP
EFI GASOLINE

0.34 M³ (12 CU FT)
CARGO BED CAPACITY

680 KG / 544 KG
(1500LB / 1200LB)
TOWING CAPACITY

545 KG / 408 KG
(1200LB / 900LB)
LOAD CAPACITY



HAULER 1200

HAULER 1200X

NEVER BE OUTWORKED

Cushman® has been trusted for decades to produce long-lasting, dependable vehicles, but that's just the start. Cushman is continually pushing forward—with the unmatched, energyefficient performance of our ELITE lithium powertrain, and better riding, better-looking, vehicles that can be customized to your needs.

KEY FEATURES

- Excellent 360 degree exterior view
- Composite noise reducing bed
- Easy ingress and regress
- Durable steel frame assures a comfortable ride
- Tight turning radius
- Tilting bed
- Increased ground clearance (1200X only)

BUILD YOUR VEHICLE

Visit [Cushman.com](https://cushman.com) to customize the vehicle for your task, by choosing the right model, powertrain, color, accessories, and more.

KEY OPTIONS & ACCESSORIES

- Ball Cage
- Aluminum Load Bed
- Electric Bed Lift
- Closed cab with doors
- Cargo Mesh Netting
- Different sizes of van boxes
- LED Headlights - High/Low Beam
- LED Taillights/ Brake Lights
- 4-Wheel Mechanical Brakes
- PACE Geofencing and GPS System

Explore all options and accessories on the website or contact your local dealer.

HAULER® 1200 / SERIES

	HAULER 1200	HAULER 1200X
BODY & CHASSIS		
FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Forest Green	
DIMENSIONS		
OVERALL LENGTH	302 cm (119 in)	
OVERALL WIDTH	125 cm (49 in)	
OVERALL HEIGHT W/CANOPY	179.1 cm (70.5 in)	196 cm (77 in)
WHEEL BASE	195 cm (76.8 in)	196.9 cm (77.5 in)
FRONT WHEEL TRACK	88.9 cm (35 in)	96.5 cm (38.0 in)
REAR WHEEL TRACK	97.8 cm (38.5 in)	
GROUND CLEARANCE	3.5 in (8.9 cm)	17.8 cm (7 in)
CARGO BED CAPACITY	0.34 m3 (12 cu ft)	
CARGO BED DIMENSIONS	99 cm (L) x 111.8 cm (W) x 30.5 cm (D) 39 in (L) x 44 in (W) x 12 in (D)	
CARGO BED MATERIAL	Roto-Molded Polyethylene	
POWER		
POWER SOURCE	4-Cycle, 401cc (24.5 ci)	
VALVE TRAIN	Single Cylinder OHV	
HORSEPOWER (KW)	10.1 kW (13.5 hp)	
ELECTRICAL SYSTEM	Starter/Generator. Solid State Reg.	
BATTERY (QTY/TYPE)	One, 12V Maintenance Free	
KEY OR PEDAL START	Pedal	
AIR CLEANER	Replaceable Industrial Rated Dry Cartridge	
LUBRICATION	Pressurized Oil System	
OIL FILTER	Spin-On	
COOLING SYSTEM	Air Cooled	
FUEL CAPACITY	25 L (6.65 Gallon) tank	
DRIVE TRAIN	Continuously Variable Transmission	
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Forward - Reverse	
REAR AXLE RATIO	11.47: 1 (Forward) 14.35:1 (Reverse)	
PERFORMANCE		
SEATING CAPACITY	2-Person	
CURB WEIGHT	445 kg (980 lb)	455 kg (1003 lb)
BED LOAD CAPACITY	363 kg (800 lb)	227 kg (500 lb)
VEHICLE LOAD CAPACITY	544 kg (1200 lb)	408 kg (900 lb)
SPEED	23.3 km/h ± 0.8 km/h (14.5 mph ± 0.5 mph)	26.6 km/h ± 0.8 km/h (16.5 mph ± 0.5 mph)
TOWING CAPACITY	680 kg (1500 lb) max	544 kg (1200 lb) max
OUTSIDE CLEARANCE CIRCLE	6.6 m (21.5 ft)	7.2 m (23.5 ft)
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Dual Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	18 x 8.5 - 8 (6 - Ply Tires)	20 x 8-10 (6 - Ply Tires)

CUSHMAN.COM