

NO TASK IS OFF LIMITS.

Every part of the Hauler 800X is designed to go the extra mile, then go 50 more. Complete with a 0.24 M³ cargo bed, bench seating, lifted suspension, and improved surface tires, the Hauler 800X approaches every job with the perfect mix of toughness and real-world utility. Available with your choice of an ELiTE lithium powertrain activated by Samsung SDI battery technology or a fuel-efficient 13.5 hp EFI gasoline engine or an ELiTE lithium powertrain activated by Samsung SDI battery technology.

O.24 M³ (8.4 CU FT) CARGO BED CAPACITY

226.8 KG (500LB)
TOWING CAPACITY

328.9 KG (725LB) VEHICLE LOAD CAPACITY

HIGHER GROUND
CLEARANCE









NEVER BE OUTWORKED

Cushman® has been trusted for decades to produce long-lasting, dependable vehicles, but that's just the start. Cushman is continually pushing forward—with the unmatched, energyefficient performance of our ELiTE lithium powertrain, and better riding, better-looking, vehicles that can be customized to your needs.

KEY FEATURES

- Excellent 360 degree exterior view
- Composite noise reducing bed
- Easy ingress and regress
- Durable steel frame assures a comfortable ride
- Tight turning radius
- Tilting bed
- Increased ground clearance

BUILD YOUR VEHICLE

Visit Cushman.com to customize the vehicle for your task, by choosing the right model, powertrain, color, accessories, and more.

KEY OPTIONS & ACCESSORIES

- Upgradeable Battery pack options (with 5-Year Battery Warranty)
- Rapid On-Board Charger (ELiTE Only)
- Aluminum Load Bed
- Electric Bed Lift
- Closed cab with doors
- Cargo Mesh Netting
- Different sizes of van boxes
- LED Headlights High/Low Beam
- LED Taillights/ Brake Lights
- 4-Wheel Mechanical Brakes
- PACE Geofencing and GPS System

Explore all options and accessories on the website or contact your local dealer.

HAULER® 800X

HAULER 800X ELITE

HAULER 800X GASOLINE

BODY & CHASSIS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Forest Green

DIMENSIONS

OVERALL LENGTH	279.4 cm (110 in)
OVERALL WIDTH	125 cm (49 in)
OVERALL HEIGHT	129.5 cm (51 in) (w/o Roof) / 188 cm (74 in) (w/ Canopy)
WHEEL BASE	166.4 cm (65.5 in)
WHEEL TRACK	94 cm (37 in) Front / 96.5 cm (38 in) Rear
GROUND CLEARANCE	14.0 cm (5.5 in)
CARGO BED CAPACITY	0.24 m3 (8.4 cu ft)
CARGO BED DIMENSIONS	72.4 cm (L) x 113 cm (W) x 30.5 cm (D) 28.5 in (L) x 44.5 in (W) x 12 in (D)
CARGO BED MATERIAL	Roto-Molded Polyethylene

POWER

POWER SOURCE	56.7V Li-Ion Battery	4-Cycle, 401cc (24.5 ci)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	8.7 kW (11.7 hp) Peak	10.1 kW (13.5 hp)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	2.2 Elite - Single Pack	One, 12V Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replaceable Industrial Rated Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	22.6 L (5.96 Gallon) tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/	Helical Gears
GEAR SELECTION	Dash Mount Forward-Neutral- Reverse / Key Switch	Forward - Reverse
REAR AXLE RATIO	16.99:1	11.47: 1 (Forward) 14.35:1 (Reverse)

PERFORMANCE

SEATING CAPACITY	2-Person (Bench)	
WEIGHT W/O BATTERIES	351 kg (744 lb)	362.9 kg (800 lb)
CURB WEIGHT	372 kg (821 lb)	376 kg (830 lb)
VEHICLE LOAD CAPACITY	328.9 kg (725 lb)	
BED LOAD CAPACITY	147.4 kg	ı (325 lb)
TOWING CAPACITY	226.8 kg (500 lb)	
OUTSIDE CLEARANCE CIRCLE	5.8 m (18.9 ft)	
SPEED	26.5 km/h ± 0.8 km/l	n (16.5 mph ± 0.5 mph)

STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	20 x 8-10 (6 Ply Rated)

CUSHMAN.COM

