



HAULER[®] 800

UNMATCHED PRODUCTIVITY STARTS HERE.

The Hauler 800, now available with an ELiTE lithium powertrain activated by Samsung SDI battery technology or with a fuel-efficient 13.5 hp EFI gasoline engine, powers through your toughest workdays. With a fully customizable cargo bed, highly functional dash and a broad range of accessories, Hauler 800 vehicles have everything you need to finish job after job.

0.24 M³ (8.4 CU FT)
CARGO BED CAPACITY

408.2 KG (900LB)
TOWING CAPACITY

362.9 KG (800LB)
VEHICLE LOAD CAPACITY

**ZERO
MAINTENANCE**
ELITE LITHIUM BATTERY

ELiTE
LITHIUM



NEVER BE OUTWORKED

Cushman® has been trusted for decades to produce long-lasting, dependable vehicles, but that's just the start. Cushman is continually pushing forward—with the unmatched, energyefficient performance of our ELITE lithium powertrain, and better riding, better-looking, vehicles that can be customized to your needs.

KEY FEATURES

- Excellent 360 degree exterior view
- Composite noise reducing bed
- Easy ingress and regress
- Durable steel frame assures a comfortable ride
- Tight turning radius
- Tilting bed

BUILD YOUR VEHICLE

Visit Cushman.com to customize the vehicle for your task, by choosing the right model, powertrain, color, accessories, and more.

KEY OPTIONS & ACCESSORIES

- Upgradeable Battery pack options (with 5-Year Battery Warranty)
- Rapid On-Board Charger (ELITE Only)
- Aluminum Load Bed
- Electric Bed Lift
- Closed cab with doors
- Cargo Mesh Netting
- Different sizes of van boxes
- LED Headlights – High/Low Beam
- LED Taillights/ Brake Lights
- 4-Wheel Mechanical Brakes
- PACE Geofencing and GPS System

Explore all options and accessories on the website or contact your local dealer.

CUSHMAN.COM

HAULER® 800

	HAULER 800 ELITE	HAULER 800 GASOLINE
BODY & CHASSIS		
FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Forest Green	
DIMENSIONS		
OVERALL LENGTH	279.4 cm (110 in)	
OVERALL WIDTH	125 cm (49 in)	
OVERALL HEIGHT	119.4 cm (47 in) (No Canopy) 176.5 cm (69.5 in) (w/ Struts & Roof)	
WHEEL BASE	166.4 cm (65.5 in)	
WHEEL TRACK	94 cm (37 in) Front / 96.5 cm (38 in) Rear	
GROUND CLEARANCE	10.9 cm (4.3 in)	
CARGO BED CAPACITY	0.24 m3 (8.4 cu ft)	
CARGO BED DIMENSIONS	72.4 cm (L) x 113 cm (W) x 30.5 cm (D) 28.5 in (L) x 44.5 in (W) x 12 in (D)	
CARGO BED MATERIAL	Roto-Molded Polyethylene	
POWER		
POWER SOURCE	56.7V Li-Ion Battery	4-Cycle, 401cc (24.5 ci)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	8.7 kW (11.7 hp) Peak	10.1 kW (13.5 hp)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	2.2 Elite - Single Pack	One, 12V Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replaceable Industrial Rated Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	22.6 L (5.96 Gallon) tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash Mount Forward-Neutral- Reverse / Key Switch	Forward - Reverse
REAR AXLE RATIO	16.99:1	11.47:1 (Forward) 14.35:1 (Reverse)
PERFORMANCE		
SEATING CAPACITY	2-Person (Bench)	
WEIGHT W/O BATTERIES	342 kg (753 lb)	345.2 kg (761 lb)
CURB WEIGHT	363 kg (800 lb)	359 kg (791 lb)
VEHICLE LOAD CAPACITY	362.9 kg (800 lb)	
BED LOAD CAPACITY	181.4 kg (400 lb)	
TOWING CAPACITY	408.2 kg (900 lb)	
OUTSIDE CLEARANCE CIRCLE	5.8 m (18.9 ft)	
SPEED	26.5 km/h ± 0.8 km/h (16.5 mph ± 0.5 mph)	23.3 km/h ± 0.8 km/h (14.5 mph ± 0.5 mph)
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack and Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	18 x 8.5 -8 (6 Ply Rated)	