



ALL-NEW

SHUTTLE™ 2+2

VERSATILITY COMMANDS THE DAY.

The newly redesigned Shuttle 2+2 is the ideal choice for transporting personnel and visitors. Comfortably seating up to four passengers with bench seats, the rear seat will also convert to a cargo deck. The Shuttle 2+2 is offered in your choice of an ELiTE lithium powertrain activated by Samsung SDI lithium technology or with a fuel-efficient 13.5-hp EFI gasoline engine.

ALL-NEW
IMPROVED STYLING

**NOW AVAILABLE
WITH**
ELITE LITHIUM
POWERTRAIN

**4 PASSENGER
SEATING**

ELiTE
LITHIUM



NEVER BE OUTWORKED

Cushman® has been trusted for decades to produce long-lasting, dependable vehicles, but that's just the start. Cushman is continually pushing forward—with the unmatched, energyefficient performance of our ELITE lithium powertrain, and better riding, better-looking, vehicles that can be customized to your needs.

KEY FEATURES

- Excellent 360 degree exterior view
- 18" or 20" Tires
- 2-Wheel Mechanical Brakes
- RFS Pro Rear-Facing Seat
- Easy ingress and regress
- Durable steel frame assure a comfortable ride

BUILD YOUR VEHICLE

Visit [Cushman.com](https://cushman.com) to customize the vehicle for your task, by choosing the right model, powertrain, color, accessories, and more.

KEY OPTIONS & ACCESSORIES

- Upgradeable Battery pack options (with 5-Year Battery Warranty)
- Rapid On-Board Charger (ELITE Only)
- Foldable rear seat
- 4-Wheel Mechanical Brakes
- Roof and Screen
- PACE Geofencing and GPS System

Explore all options and accessories on the website or contact your local dealer.

CUSHMAN.COM

ALL-NEW SHUTTLE™ 2+2

SHUTTLE 2+2 ELITE		SHUTTLE 2+2 GASOLINE	
18" TIRES	20" TIRES	18" TIRES	20" TIRES

BODY & CHASSIS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat			
BODY & FINISH	Injection Molded TPO			
STANDARD COLOR	Patriot Blue			

DIMENSIONS

OVERALL LENGTH	(287 cm (113 in))			
OVERALL WIDTH	119 cm (47 in)			
OVERALL HEIGHT (W/ CANOPY)	193 cm (76 in)	203 cm (80 in)	193 cm (76 in)	203 cm (80 in)
OVERALL HEIGHT (W/O CANOPY)	122 cm (48 in)	132 cm (52 in)	122 cm (48 in)	132 cm (52 in)
WHEEL BASE	166 cm (65.5 in)			
WHEEL TRACK	94 cm (37 in) Front / 97 cm (38 in) Rear			
GROUND CLEARANCE	11 cm (4.3 in)	14 cm (5.5 in)	11 cm (4.3 in)	14 cm (5.5 in)

POWER

POWER SOURCE	56.7V Li-Ion Battery	4-Cycle, 401cc (24.5 ci)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	8.7 kW (11.7 hp)	10.1 kW (13.5 hp)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator, Solid State Regulator
BATTERY (QTY/TYPE)	2.2 Single, 56.7V Li-Ion Composite Module	One, 12V Maintenance Free
BATTERY CHARGER	56.7V, 350W Domestic Charger, 3M Charging Cord	N/A
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Industrial Rated Dry Filter
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	22.6 L (5.96 Gallon) tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash Mount Forward-Neutral-Reverse / Key Switch	Forward - Reverse
REAR AXLE RATIO	16.99:1	11.47:1 (Forward) / 14.35:1 (Reverse)

PERFORMANCE

SEATING CAPACITY	4-Person			
WEIGHT W/O BATTERIES	342 kg (743 lb)	351 kg (782 lb)	396 kg (872 lb)	414 kg (913 lb)
CURB WEIGHT	363 kg (790 lb)	372 kg (829 lb)	409 kg (902 lb)	437 kg (963 lb)
VEHICLE LOAD CAPACITY	363 kg (800 lb)			
OUTSIDE CLEARANCE CIRCLE	5.76 m (18.9 ft)			
SPEED	26.5 km/h ± 0.8 km/h (16.5 mph ± 0.5 mph)			

STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion			
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers			
SERVICE BRAKE	Dual Rear Wheel Mechanical Self-adjusting Drum			
PARKING BRAKE	Self-Compensating, Single-Point Engagement			
TIRES (FRONT & REAR)	Hole-N-One Tires	K399, 205/65-10, 6 PLY	Hole-N-One Tires	K399, 205/65-10, 6 PLY