



# SHUTTLE™ 2

## DELIVER HARD WORK.

Move large materials around your facility with the Shuttle 2. Utilize the 544 kg cargo capacity and a 1.94 M<sup>2</sup> cargo deck to move anything from lumber to luggage. The Shuttle 2 is available with an ELiTE lithium powertrain activated by Samsung SDI technology or a 13.5 hp EFI gasoline engine, both offering sufficient power to get the job done.

**EXTENDED**  
CARGO DECK AND  
WHEEL BASE

**544 KG (1200LB)**  
VEHICLE LOAD CAPACITY

**1.94 M<sup>2</sup> (20.9 SQ FT)**  
CARGO DECK CAPACITY

**ELiTE**  
LITHIUM

Photo note: Shuttle 2 comes standard with 137 cm (54") roof. Vehicle shown above with 208 cm (82") roof.



# SHUTTLE™ 2

## SHUTTLE 2 ELITE

## SHUTTLE 2 GASOLINE

### BODY & CHASSIS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Patriot Blue	

### DIMENSIONS

OVERALL LENGTH	358 cm (141.0 in)	
OVERALL WIDTH	123 cm (48.5 in)	
OVERALL HEIGHT	123 cm (48.6 in) (w/o Roof) / 183 cm (72.0 in) (w/ Struts & Roof)	
WHEEL BASE	237 cm (93.5 in)	
WHEEL TRACK	87 cm (34.2 in) Front / 97 cm (38.0 in) Rear	
GROUND CLEARANCE	11 cm (4.3 in)	9.8 cm (3.9 in)
CARGO DECK CAPACITY	1.94 m <sup>2</sup> (20.9 sq ft)	

### POWER

POWER SOURCE	56.7V Li-Ion Battery	4-Cycle, 401cc (24.5 ci)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	13.5 kW (18.1 hp) @ 1900 rpm	10.1 kW (13.5 hp)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	Single, 56.7V max Li-Ion Composite Module and Cell Module ("Twin Pack")	One, 12V Maintenance Free
BATTERY CHARGER	56.7V, 811W World Charger, 3M Charging Cord	N/A
KEY OR PEDAL START		Pedal
AIR CLEANER	N/A	Replaceable Industrial Rated Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	22.7 L (6 Gallon) Tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Limited-Slip Differential with Helical Gears	Differential with Helical Gears
GEAR SELECTION	Dash Mount Forward-Neutral-Reverse / Key Switch	Forward - Reverse
REAR AXLE RATIO	16.99:1	11.47: 1 (Forward) / 14.35:1 (Reverse)

### PERFORMANCE

SEATING CAPACITY	2-Person	
WEIGHT W/O BATTERIES	367 kg (810 lb)	420 kg (926 lb)
CURB WEIGHT	590 kg (1300 lb)	
VEHICLE LOAD CAPACITY	544 kg (1200 lb)	
BED LOAD CAPACITY	363 kg (800 lb)	
OUTSIDE CLEARANCE CIRCLE	7.8 m (25.5 ft)	
SPEED	(26.4 km/h ± 0.8 km/h) 16.5 mph ± 0.5 mph	(22.5 km/h ± 0.8 km/h) 14 mph ± 0.5 mph

### STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum	
PARKING BRAKE	Automatic Electro-Magnetic	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	18 x 8.50 - 8 (4 Ply Rated)	

### NEVER BE OUTWORKED

Cushman® has been trusted for decades to produce long-lasting, dependable vehicles, but that's just the start. Cushman is continually pushing forward—with the unmatched, energyefficient performance of our ELITE lithium powertrain, and better riding, better-looking, vehicles that can be customized to your needs.

### KEY FEATURES

- Extended cargo deck
- Extended wheel base
- Excellent 360 degree exterior view
- Easy ingress and regress
- Durable steel frame assure a comfortable ride

### BUILD YOUR VEHICLE

Visit [Cushman.com](http://Cushman.com) to customize the vehicle for your task, by choosing the right model, powertrain, color, accessories, and more.

### KEY OPTIONS & ACCESSORIES

- Upgradeable Battery pack options (with 5-Year Battery Warranty)
- Rapid On-Board Charger (ELITE Only)
- Drop Side Rails
- Front Disc Brakes
- Turn Signal with Four-Way Flashers
- Strobe Lights
- Beacon Light Kit
- Dome and Work Lights
- Roof and Screen
- PACE Geofencing and GPS System

Explore all options and accessories on the website or contact your local dealer.

Photo note: Shuttle 2 comes standard with 137 cm (54") roof. Vehicle shown above with 208 cm (82") roof.

## CUSHMAN.COM